

Technical Specification of CVD Machines – HT2439

CVD/CVI Reactor for SiC, C and BN

The HT 2439 is designed for the CVD/CVI of silicon carbide and boron nitride. It has a rotating platform to permit the overall coating of parts weighing up to 300kg in a single cycle. A PLC control system runs the cycle without any operator intervention. The all carbon, working zone is suitable for operation up to 1,600°C at pressures between 1 and 1000mbar.



Overview

The CVD/CVI system HT 2439 has a graphite working chamber of 700 x 1000 mm high. This is surrounded by two independent resistance heaters controlled by thermocouples and two colour pyrometers. Thermal insulation is provided by ceramic fibre, all contained in a stainless steel vacuum vessel and water-jacketed. The main axis of the chamber is vertical and is accessed from the top.

The reactor is evacuated by a liquid ring pump plus two mechanical boosters. The booster pumps both have bypass valves so that a number of different pump combinations can be run.

It has a scrubbing utility that ensures a clean effluent gas.

The gas delivery system will handle six gas flows (CH_4 , H_2 , Ar , N_2 , NH_3 , BCl_3) and one gas from a liquid source evaporator for CH_3SiCl_3 (MTS). All gas flows have mass flow controllers. There are two feed lines to the reactor to permit delayed mixing of the reactants-necessary for BN.

The control system is supervised by a PLC microprocessor that will run complete cycles without the need for operator intervention. All process parameters are monitored and any variation outside of chosen limits initiates a safe shutdown procedure. The control system is usually installed remote from the rest of the machine for increased safety.



CVD.CO.UK




Archer Technicoat Ltd.

Progress Road, Sands Industrial Estate,
High Wycombe, Buckinghamshire, HP12 4JD
Tel. +44 (0) 1494 462101 Fax +44 (0) 1494 463049
www.cvd.co.uk

Specification

Criteria	Specification
Reactor Overall Dimensions	10 x 7 x 6m high+ height above for loading
Reactor Working Zone	700 diameter x 1000mm top loading
Temperature Range	900-1600°C
Temperature Measurement	2-colour pyrometer or thermocouple
Pressure Range	1-100mbar (standard control range)
Pressure Measurement	Absolute pressure transducer
Feed Gases	H ₂ , Ar, CH ₄ , NH ₃ , BCl ₃
Feed Liquids	SiCl ₄ , CH ₃ , SiCl ₃
Flow Control	Mass flow controllers
Vacuum Pumps	Liquid ring vacuum pump - 260m ³ /hr @ 50Hz Mechanical booster pump 1 – 1,220m ³ /hr @ 50Hz Mechanical booster pump 2 – 4,280m ³ /hr @ 50Hz Automatic pressure control by servo controlled line valve.
Materials of Construction	Vacuum vessel - 316 stainless steel Heater - graphite Reactor inner chamber - graphite Thermal insulation – ceramic or carbon fibre
Electricity	225KVA (3-phase)
Cooling Water	80litre/min
Compressed Air	100 p.s.i. small amount for actuators
Effluent Scrubber	Wet scrubbing column with 1,500L tank. Continuous pH monitoring & control.

CVD/CVI Processes



Archer Technicoat Ltd.

Progress Road, Sands Industrial Estate,
High Wycombe, Buckinghamshire, HP12 4JD
Tel. +44 (0) 1494 462101 Fax +44 (0) 1494 463049
www.cvd.co.uk